



Base Roscada GPL F

Grupo: A838

Aplicação

Elemento para a fixação de abraçadeiras a Perfis F 80 ou F 100, através de tubo roscado de 1/2" ou conexão roscada M16.

Instalação

Requer 2 parafusos FLS por Base Roscada GPL.

Dados Técnicos

Tipo	Tensão [kN]	Força Lateral [kN]	Momento fletor admissível [Nm]
GPL F 80-1/2"	8,0	13,0	53
GPL F 80-M10	8,0	13,0	15
GPL F 80-M12	8,0	13,0	26
GPL F 80-M16	8,0	13,0	62
GPL F 100-1/2"	8,0	13,0	53
GPL F 100-M10	8,0	13,0	15
GPL F 100-M12	8,0	13,0	26
GPL F 100-M16	8,0	13,0	62

Dimensões placa base: GPL F 80: 80 x 50 x 4 mm
 Dimensões placa base: GPL F 100: 100 x 50 x 4 mm
 Material: Aço, HCP

Tipo	Peso [kg]	Quant. [caixa]	Código
GPL F 80-1/2"	0,1	50	192900
GPL F 80-M10	0,1	50	113004
GPL F 80-M12	0,1	50	112911
GPL F 80-M16	0,1	50	195833
GPL F 100-1/2"	0,2	50	113089
GPL F 100-M10	0,2	50	113338
GPL F 100-M12	0,2	50	113646
GPL F 100-M16	0,2	50	113090